

Accessories

Controls

<p>B0999</p>	<p>Wireless control for radiators When installed on existing radiators, it can be wirelessly connected to the heat pump air conditioner via the home wireless network. Controllable via the OS Home app, allowing for scenarios to be programmed that activate one of the two heating systems based on specific conditions. Compatible with the main valve bodies available on the market and easily replaceable with the existing manual valve or traditional thermostatic control already installed on the radiators.</p>	<p>NEW</p> 
<p>B1029</p>	<p>Wireless thermostat Wireless wall control with black and white display (wireless to Unico and equipped with OS Smart System app), complete with receiver to be installed on Unico. Battery operated. Equipped with temperature measurement.</p>	
<p>B1030</p>	<p>IAQ wireless thermostat Wireless colour wall control (wireless to Unico and equipped with OS Smart System app), complete with receiver to be installed on Unico. Mains powered, can be installed on 503 electrical box and on round box. Equipped with temperature, humidity and internal air quality measurement.</p>	
<p>B1128</p>	<p>Relay wireless To wirelessly control other generators or external electrical heating elements, based on the external temperature and the difference between the internal temperature and the set-point temperature.</p>	
<p>B1015</p>	<p>Wireless kit Wireless/bluetooth interface board to integrate connectivity into units when it is not present.</p>	
<p>B1014</p>	<p>Wireless serial interface Interface for receiving wireless commands (desired temperature, ventilation speed, air deflector operation and air change function) or via contacts (Cooling or Heating operating mode, ventilation speed). Presence sensor contact or Sleep mode. Alarm output in case of malfunction.</p>	
<p>B1012</p>	<p>Wireless wall control Battery-powered wall-mounted control for sending wireless commands (desired temperature, ventilation speed, air deflector operation).</p>	

Installation kit

<p>B0984</p>	<p>Kit for preparing holes with a diameter of 200 mm Kit for preparing holes with a diameter of 200 mm equipped with a pair of 200mm folding grids, a pair of 200mm internal flanges, a pair of universal PP sheets, templates for each compatible model (there are no support brackets, which are included in the machine packaging).</p>	
<p>B0564</p>	<p>Grille kit diameter 160 mm Pair of inside flanges Ø 160 mm, pair of outside folding grilles Ø 160 mm.</p>	

Installation kit

B0620 Heating cable

To prevent the formation of ice in the condensation trap for drainage (heating cable already standard on Unico Vertical).



B0753

Rain cover kit for 200 mm grilles

To be installed on the outside wall to protect the holes (for installations in extreme weather conditions). Designed for \varnothing 200 mm grilles. This product is available by special order only. The packaging contains 2 elements (1 for each hole).



Recess kit

B0776

Recessed closing panel

Designed to completely blend Unico Air into the building architecture.



B0775

Recessed formwork

Supplied for quick installation of Unico Air, pre-drilled for product installation.



B1032

Wall recess kit

Metal panel with delivery and extraction grille that can be used for built-in installations of Unico Vertical-NK.



B1033

Wall recess kit with HRV kit

Metal panel with delivery and return air grille, that can be used for recessed installation of Unico Vertical-NK when combined with the HRV kit (B1031).



HRV kit

B1031

HRV kit

Crossflow enthalpic heat recovery unit for air exchange, ducted extraction and delivery through Unico Vertical-NK delivery grille. Maximum flow rate at 100 Pa equal to 103 m³/h. Can be controlled in combination with Unico Vertical-NK from the Wireless IAQ control (code B1030).



B0998

Kit for 160mm grille for HRV installation

Kit for holes with diameter 160 mm for HRV (code B1031) equipped with a pair of folding grilles d. 160mm, a pair of internal flanges d. 160mm, a pair of universal PP sheets.

