EVAPORATIVE COOLERS

PELER 40

Size	**40**
Operation without water	✓

Important airflow

Up to 1,800 m³/h at a maximum speed of 7 m/s: a vortex system that generates a significant airflow, capable of covering distances up to 14.4 metres. Ideal for cooling large residential and non-residential environments (shops, restaurants and outdoor areas), with long operating autonomy thanks to the large 40-litre tank.

Automatic drying

To prevent the formation of mould and bacteria during periods of non-use, the system is equipped with an automatic drying function for the evaporative panels.

TECHNICAL INFO

- Filling directly from the canister (with flashing light to indicate lack of water) and emptying via special cap.
- Electrostatic filter with anti-dust function and 3 honeycomb evaporative panels.
- Pump protection system.
- 3 ventilation speeds (low, medium, high).
- Wheels for easy transportation.
- Ice boxes included.

Evaporation (with water)

Ventilation (without water)

Dry Air

Natural Wind

Normal Wind

Sleep Wind

Horizontal swing

Timer

TECHNICAL DATA

			Peler 4T	Peler 7T	Peler Tower 10
Product code			99211	99210	99208
EAN code			8021183992113	8021183992106	8021183992083
Electrical power supply		V/F/Hz	220-240 /1/50 - 60	220-240 /1/50 - 60	220-240 /1/50 - 60
Maximum power absorption		W	60	80	38
Stand-by power consumption		W	-	0,2	0,4
Fan speed		n	3	3	24
Air flow rate (maximum)		m³/h	140	300	1000
Air speed (maximum)		m/s	7,2	7	6,5
Maximum sound pressure level	(1)	dB(A)	45	60	55
Maximum sound power level	(1)	dB(A)	🔊 60	🔊 60	🔊 63
Insulation class			II	II	II
Power cable		n / mm²	2 x 0,75	2 x 0,75	2 x 0,75
Water tank capacity		l	3,8	7	10
Evaporative sheet			Honeycomb	Honeycomb	Honeycomb
Control panel			Touch	Touch	Digital
Conformity mark			CE	CE	CE
Dimensions (WxHxD)		mm	260 x 600 x 232	235 x 567 x 260	309 x 938 x 279
Gift box dimensions (WxHxD)		mm	293 x 630 x 265	286 x 593 x 311	340 x 775 x 330
Weight (without packaging)		kg	4,0	3,6	6,1
Weight (with packaging)		kg	5,3	4,4	8,5
Timer			√	√	√
Removable water tank			√	-	√
Oscillating function			√	√	√
Remote control			√	√	√
Ionizer			-	-	-
Power off switch			-	-	-
Power supply cable housing			-	-	-
Wireless control			-	-	-

TECHNICAL DATA

			Peler 25 Wifi	Peler 40
Product code			99209	99207
EAN code			8021183992090	8021183992076
Electrical power supply		V/F/Hz	220-240 /1/50 - 60	220-240 /1/50 - 60
Maximum power absorption		W	90	120
Stand-by power consumption		W	0,5	0,5
Fan speed		n	3	3
Air flow rate (maximum)		m³/h	1500	1800
Air speed (maximum)		m/s	8,0	7,0
Maximum sound pressure level	(1)	dB(A)	44	65
Maximum sound power level	(1)	dB(A)	🔊 58	🔊 65
Insulation class			II	II
Power cable		n / mm²	2 x 0,75	2 x 0,75
Water tank capacity		l	25	40
Evaporative sheet			Honeycomb	Honeycomb
Control panel			Digital	Touch
Conformity mark			CE	CE
Dimensions (WxHxD)		mm	333 x 840 x 418	485 x 1009 x 403
Gift box dimensions (WxHxD)		mm	386 x 600 x 454	560 x 1090 x 490
Weight (without packaging)		kg	7,1	14,1
Weight (with packaging)		kg	10,5	18,0
Timer			√	√
Removable water tank			√	-
Oscillating function			√	√
Remote control			√	√
Ionizer			√	-
Power off switch			-	-
Power supply cable housing			-	-
Wireless control			√	-

(1) Test conditions: the sound pressure level was measured in a semi-anechoic chamber at a distance of 2 metre from the front of the unit, with the microphone positioned at a height of 1 metre. During measurement, all unit functions are enabled except oscillation (if present).